

規格表

2015.11.26

型號	伏特	端子 位置	容量 A/Hr Pb Eq	CCA (A)	重量 (kg)	長 mm	寬 mm	高 mm
LFX07L2-BS12	12 V		7	102	0.483	113	58	89
LFX09A2-BS12	12 V		9	135	0.575	113	58	89
LFX09L2-BS12	12 V		9	135	0.575	113	58	89
LFX12A1-BS12	12 V		12	155	0.6125	148	66	105
LFX14A1-BS12	12 V		14	210	0.763	148	66	105
LFX14A2-BS12	12 V		14	210	0.575	113	58	89
LFX14A4-BS12	12 V		14	210	0.901	148	86	88
LFX14A5-BS12	12 V		14	210	1.032	134	80	160
LFX14L2-BS12	12 V		14	210	0.763	113	58	89
LFX14L5-BS12	12 V		14	210	1.032	134	80	160
LFX18A1-BS12	12 V		18	270	0.997	148	66	105
LFX18L1-BS12	12 V		18	270	0.997	148	66	105
LFX19A4-BS12	12 V		19	285	1.050	148	86	88
LFX21A6-BS12	12 V		21	315	1.4	148	82	140
LFX21L6-BS12	12 V		21	315	1.4	148	82	140
LFX24A3-BS12	12 V		24	360	1.8	166	86	155
LFX24L3-BS12	12 V		24	360	1.8	166	86	155
LFX27A3-BS12	12 V		27	405	1.9	166	86	155
LFX27L3-BS12	12 V		27	405	1.9	166	86	155
LFX36A3-BS12	12 V		36	540	2.25	166	86	155
LFX36L3-BS12	12 V		36	540	2.25	166	86	155
LFX18A2-BS06	6 V		18	270	0.575	113	58	89
LFX18L2-BS06	6 V		18	270	0.575	113	58	89



